

DE5a-Net



OpenCL



terasic

www.terasic.com

Copyright © 2003-2016 Terasic Inc. All Rights Reserved.

CONTENTS

CHAPTER 1	<i>DE5A-NET OPENCL</i>	3
1.1	SYSTEM REQUIREMENT	3
1.2	OPENCL ARCHITECTURE	4
CHAPTER 2	<i>OPENCL FOR WINDOWS</i>	5
2.1	SOFTWARE INSTALLATION	5
2.2	OPENCL LICENSE INSTALLATION	7
2.3	CONFIGURE	8
2.4	BOARD SETUP	11
2.5	OPENCL ENVIRONMENT VERIFY AND FLASH CVP	12
2.6	COMPILE AND TEST OPENCL PROJECT	16
CHAPTER 3	<i>OPENCL FOR LINUX</i>	19
3.1	SOFTWARE INSTALLATION	19
3.2	OPENCL LICENSE INSTALLATION	22
3.3	CONFIGURE	22
3.4	BOARD SETUP	23
3.5	OPENCL ENVIRONMENT VERIFY AND FLASH CVP	24
3.6	COMPILE AND TEST OPENCL PROJECT	29

Chapter 1

DE5a-Net OpenCL

DE5a-Net, an unparalleled and powerful platform for high-speed computation, is now officially also an Altera certified board for Intel's Preferred Board Partner Program for OpenCL. It supports both 64-bit Windows and Linux. This document will introduce you how to setup OpenCL development environment for DE5a-Net board, and how to compile and execute the example projects for DE5a-Net. Note that OpenCL coding instruction is not in the scope of this document, but the user can refer to Altera SDK for OpenCL Programming Guide for more details.

https://www.altera.com/en_US/pdfs/literature/hb/opencl-sdk/aocl_programming_guide.pdf

1.1 System Requirement

The following items are required to set up OpenCL for DE5a-Net board:

- DE5a-Net Board with one 4GB DDR3-SODIMM installed on DDR3-SODIMM-A port.
- A Host PC with
 - USB Host Port
 - One PCI Express x8/x16 slot with 12V power pin
 - 32GB memory is recommended, 24GB is minimal
 - 2x3 pin 12V Power for DE5a-Net (optional)
- An USB Cable(type A to mini-B)
- 64-bit Windows7/10 or Linux(Redhat 6.5/CentOS 7.0) Installed
- Altera Quartus II Pro Edition (Version 16.0.2 Build 222) Installed, licensed is required
- Altera SDK for OpenCL (Version 16.0.2 Build 222) Installed, license is required
- DE5a-Net OpenCL BSP 16.0 Installed
- Visual Studio 2012 C/C++ installed for Windows7/10
- GNU development tools for Linux

Note:

1. Altera OpenCL only supports 64-bit OS and x86 architecture.
2. We strongly recommend setting the PCIe speed to **Gen3x8** in your PC BIOS for good performance.

1.2 OpenCL Architecture

An OpenCL project is composed of both OpenCL Kernel and Host Program as shown in **Figure 1-1**. OpenCL kernel is compiled with Altera OpenCL compiler provided by the Altera OpenCL SDK. The Host Program is compiled by Visual Studio C/C++ in Windows or GCC on Linux.




Figure 1-1 Altera OpenCL Architecture

Chapter 2

OpenCL for Windows

This chapter describes how to set up DE5a-Net OpenCL development environment on 64-bit Windows, and how to compile and test the OpenCL examples for DE5a-Net. For more details about Altera OpenCL started guide, please refer to:

https://www.altera.com/en_US/pdfs/literature/hb/opencl-sdk/aocl_getting_started.pdf

2.1 Software Installation

This section describes where to get the required softwares for OpenCL.

■ **Altera Quartus II and OpenCL SDK**

Altera Quartus II Pro Edition Build 211 can be download from the web site:

<http://dl.altera.com/16.0/pro>

For Quartus II installation, please make sure that the Arria 10 device is included.

Altera Quartus II Pro Edition Build 222 and OpenCL SDK Build 222 windows update files can be download from the web site:

<http://dl.altera.com/opencl/16.0/>

open the link and select the **Updates** table as **Figure2-1** shows.

Design Software
Embedded Software
Archives
Licensing
Programming Software
Drivers
Board System Design
Board Layout and Test
Legacy Software

Intel SDK for OpenCL™

Release date: May, 2016
Latest Release: v16.1

Select release:

Download Method Akamai DLM3 Download Manager Direct Download

Windows SDK | Linux SDK | RTE | Updates

Download and install instructions: [Less](#)

1. If you haven't already installed the Quartus II software v16.0 and the Intel FPGA SDK for OpenCL, download and install them.
2. Download the software update file.
3. Change the file permission for all the setup (.run) files by running the command: `chmod +x *.run`.
4. Run the file.

[Read Intel FPGA SDK for OpenCL Getting Started Guide](#)
To learn more about the contents of the software update, refer to the [release notes](#).

Windows Update Files

- Software and IP Updates (Latest)**
 - Quartus Prime Software v16.0 Update 2**
*You must have the base software installed before installing the update.
Size: 6.4 GB MD5: 00888D559E5D24785B21F0022DE9018B
 - Altera SDK for OpenCL v16.0 Update 2**
Size: 194.1 MB MD5: AC3895C245532B39055A56FE442DA868

Figure 2-1 Windows Update Files

■ Visual Studio 2012

If developers don't have Visual studio C/C++ 2012, they can use the trial version of Visual Studio 2012 Express. The software can be downloaded from the web site:

<http://www.microsoft.com/en-us/download/details.aspx?id=34673>

■ DE5a-Net OpenCL BSP (Board Support Package)

After Quartus II and OpenCL SDK are installed, download the DE5ANET_I2_OpenCL_BSP_16.0.zip DE5a-Net windows BSP for Altera OpenCL 16.0 from the web:

<http://de5a-net.terasic.com/cd>

Then, decompress DE5ANET_I2_OpenCL_BSP_16.0.zip to the “**de5a_net_i2**” folder under the folder “C:\altera_pro\16.0\hld\board”, as shown in **Figure 2-**, where assumed Quartus II is installed on the folder “C:\altera_pro\16.0”.




Figure 2-2 DE5a-Net OpenCL BSP Content

2.2 OpenCL License Installation

An OpenCL license is required for Altera OpenCL SDK to compile any OpenCL projects successfully. Developers can purchase the OpenCL license from either Altera or Terasic. Assuming that developers have obtained a license file with the filename “license.dat”, and it is saved in the local disk with the file path such as “c:\license.dat”. The license can then be set up by creating an environment variable **LM_LICENSE_FILE**, and set its value as “c:\license.dat”. Note that this environment value needs to correspond to the actual “license.dat” file location.

Now, here are the procedures to create the required **LM_LICENSE_FILE** environment variable on Windows 7:

1. Open the Start Menu and right click on **Computer**. Select **Properties**.
2. Select **Advanced system settings**.
3. In the **Advanced** tab, select **Environment Variables**.
4. Select **New**.
5. In the popup **New User Variable** dialog as shown in **Figure 2-**, type “**LM_LICENSE_FILE**” in the **Variable name** edit box and type “**c:\license.dat**” in the Variable value edit box.




Figure 2-3 Setup LM_LICENSE_FILE Environment Variable

2.3 Configure

For Altera OpenCL SDK to be able to find the kit location of DE5a-Net correctly, developers need to create an environment variable **AOCL_BOARD_PACKAGE_ROOT**, and set its value as:

```
“%ALTEAOCLSDKROOT%\board\de5a_net_i2”
```

Also, append "%AOCL_BOARD_PACKAGE_ROOT%\windows64\bin" and "%ALTEAOCLSDKROOT%\bin" and "%ALTEAOCLSDKROOT%\windows64\bin" into the **PATH** environment variable so the OpenCL SDK can find the binary file provided by DE5a-Net BSP.

Here are the procedures to create the required **AOCL_BOARD_PACKAGE_ROOT** environment variable on Windows 7:

1. Open the Start Menu and right click on **Computer**. Select **Properties**.
2. Select **Advanced system settings**.
3. In the **Advanced** tab, select **Environment Variables**.
4. Select **New**.
5. In the popup **New User Variable** dialog as shown in **Figure 2-**, type “**AOCL_BOARD_PACKAGE_ROOT**” in the **Variable name** edit box and type “%ALTEAOCLSDKROOT%\board\de5a_net_i2” in the **Variable value** edit box.
6. In Command Prompt window, type “**aocl install**” to install PCI Express driver. Note that users need to have administrator privileges to install the driver.




Figure 2-4 Setup AOCL_BOARD_PACKAGE_ROOT Environment Variable

Here are the procedures to add "%AOCL_BOARD_PACKAGE_ROOT%\windows64\bin" and "%ALTERAOCLSDKROOT%\bin" and "%ALTERAOCLSDKROOT%\windows64\bin" into the **PATH** environment variable on Windows 7:

1. Open the Start Menu and right click on **Computer**. Select **Properties**.
2. Select **Advanced system settings**.
3. In the **Advanced** tab, select **Environment Variables**.
4. In the Environment Variables window (as shown below), highlight the **Path** variable in the Systems Variable section and click the **Edit** button as shown in **Figure 2-**.
5. In the Edit dialog, Append “%AOCL_BOARD_PACKAGE_ROOT%\windows64\bin; %ALTERAOCLSDKROOT%\bin; %ALTERAOCLSDKROOT%\windows64\bin” into the Variable value edit box. Note, each different directory should be separated with a semicolon as shown in **Figure 2-**.




Figure 2-5 Select “Path” and click “Edit” bottom




Figure 2-6 Edit PATH environment variable

2.4 Board Setup

Before testing OpenCL on DE5a-Net, please follow the below procedures to set up DE5a-Net board on your PC as shown in [Figure 2-](#).

1. Make sure your PC is powered off.
2. Insert DE5a-Net board into PCI Express x8 or x16 slot.
3. Connect PC's 12V PCI Express 6-pin power source to the DE5a-Net
4. Connect PC's USB port to DE5a-Net mini USB port using an USB cable.

Note, the usb cable can be removed later if OpenCL code had been programming to the startup configuration flash of DE5a-Net by 'aocl flash' command.




Figure 2-7 Setup DE5a-Net board on PC

2.5 OpenCL Environment Verify and Flash CvP

This section will show how to make sure the OpenCL environment is setup correctly. Firstly, please open **Command Prompt** windows by click Windows **Start** button, clicking **All Programs**, clicking **Accessories**, and then click **Command Prompt**.

■ Target Board

In Command Prompt window, type “**aoc --list-boards**” command, and make sure “**de5a_net_i2**” is listed in **Board list** as shown in **Figure 2-**.



```
Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>aoc --list-boards
Board list:
  de5a_net_i2

C:\Users\Administrator>
```

Figure 2-8 ‘de5a_net_i2’ is listed in Board list

■ Test ‘aocl flash’ Command

In Command Prompt window, type ”cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin” to go to hello world OpenCL project folder.

Then type “**aocl flash acld5a_net0 hello_world.aocx**” to write **hello_world.aocx** OpenCL image onto the startup configuration flash of DE5a-Net. Before flash programming, the programmer will ask users which startup configuration image area will be used as shown in **Figure 2-**. This is because DE5a-Net provides two startup configuration image areas, called as Factory Image and User Image. We recommend users to key in ‘1’ to select User Image area.

```

Administrator: C:\Windows\system32\cmd.exe
C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin>"C:/altera_pro/16
.0/quartus"\bin64\perl\bin\perl "C:\altera_pro\16.0\hld\board\de5a_net_i2"\windo
ws64\libexec\flash.pl aclde5a_net0 C:\Users\ADMINI~1\AppData\Local\Temp\3592Comm
andpm521_1483608347_0_fpga_temp.bin
===== Page Selection =====
Please select the flash page where to store your FPGA configure data:
[0] Factory Image Location(Address 0x00040000), SW3.4 = "1" (Down Position)
[1] User Image Location(Address 0x02B40000), SW3.4 = "0" (Up Position)
Enter a digital number 0 or 1 (Or other values to exit the program) followed by
pressing the "Enter" key:
1
Flash Programming...
Info: *****
Info: Running Quartus Prime Convert_programming file
Info: Version 16.0.2 Build 222 07/20/2016 SJ Pro Edition
Info: Copyright (C) 1991-2016 Altera Corporation. All rights reserved.
Info: Your use of Altera Corporation's design tools, logic functions
Info: and other software and tools, and its AMPP partner logic
Info: functions, and any output files from any of the foregoing
Info: (including device programming or simulation files), and any
Info: associated documentation or information are expressly subject
Info: to the terms and conditions of the Altera Program License
Info: Subscription Agreement, the Altera Quartus Prime License Agreement,
Info: the Altera MegaCore Function License Agreement, or other

```

Figure 2-9 Select Flash Page

After users select desired flash area, it will take about 20 minutes for flash programming. **Figure 2-** is the screen shot when flash programming is done successfully.

```

F80000
Info (209005): Programming status: programming flash memory at byte address 0x0F
F90000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FA0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FB0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FC0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FD0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FE0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FF0000
Info (209011): Successfully performed operation(s)
Info (209061): Ended Programmer operation at Mon Nov 10 18:07:25 2016
Info: Quartus II 64-Bit Programmer was successful. 0 errors, 0 warnings
Info: Peak virtual memory: 2551 megabytes
Info: Processing ended: Mon Nov 10 18:07:25 2016
Info: Elapsed time: 00:38:52
Info: Total CPU time (on all processors): 00:00:34
C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin>

```

Figure 2-10 aocl flash aclde5a_net0 hello_world.aocx” successfully

To make sure a correct image is used when FPGA boots up, please make sure the dip switch SW3.4 on DE5a-Net is changed to the correct location. If a User Image area is selected, the dip switch SW3.4 on the DE5a-Net should be moved to **Up** position as shown in **Figure 2-2**.




Figure 2-2 Set SW3.4 to Up Position (User Image Page)

After flash programming is done successfully and SW3.4 is set to correct position, developers can power off PC and DE5a-Net board, then turn it back on.

■ Test ‘aocl diagnose’ Command

The diagnose utility in the Arria 10 DE5a-Net board reports device information and identifies issues. The diagnose utility first verifies the installation of the kernel driver and returns the overall information of all the devices installed in a host machine.

In Command Prompt window, type ”**aocl diagnose**” to check if the initialization completed successfully. If successful, the programming message displays “**DIAGNOSTIC_PASSED**” as shown in [Figure 2-12](#).

```

Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>aocl diagnose
aocl diagnose: Running diagnose from C:\altera_pro\16.0\h1d\board\de5a_net_i2/windows64/libexec

----- ac10 -----
Vendor: Terasic

Phys Dev Name  Status  Information
-----
aclde5a_net0  Passed  Arria 10 Reference Platform (aclde5a_net0)
                                     PCIe dev_id = 2494, bus:slot.func = 01:00.00, Gen3 x8
                                     FPGA temperature = 36.75 degrees C.

DIAGNOSTIC_PASSED

-----


C:\Users\Administrator>
  
```

Figure 2-12 “aocl diagnose” messages

Note: For DE5a-Net to negotiate with the host PC at Gen 3 as the link speed, it is strongly recommended that users set the PCIe speed at Gen 3 in the BIOS on the host PC. If your PC support PCIe Gen3x8, but it gets incorrect detected information, you can modify the PCIe settings in the BIOS, and reboot.

■ Test ‘aocl program’ Command

Check whether the **hello_world** OpenCL image, which is CvP enabled, configures the FPGA successfully. In Command Prompt window, type "cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin" to go to **hello_world\bin** project folder, then type "**aocl program alcd**e5a_net0 **hello_world.aocx**" to configure the FPGA with **hello_world.aocx** OpenCL image. If the programming message displays "Program succeed" as shown in **Figure 2-3**, it means the **hello_world** OpenCL image is programmed into the flash correctly and CvP works well.



```
Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_w
orld\bin

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin>aocl program alcd
e5a_net0 hello_world.aocx
aocl program: Running program from C:\altera_pro\16.0\hld\board\de5a_net_i2\wind
ows64\libexec
Setting debug level to 0
Failed to find requested device alcd e5a_net0 from 1 devices
aocl program: Program failed.

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\hello_world\bin>
```

Figure 2-3 “aocl program alcd e5a_net0 hello_world.aocx” use CvP


2.6 Compile and Test OpenCL Project

This section will show how to compile and test OpenCL kernel and OpenCL Host Program for the vector_add project. Developers can use the same procedures to compile and test other OpenCL examples for DE5a-Net.

■ Compile OpenCL Kernel

The utility **aoc** (Altera SDK for OpenCL Kernel Compiler) is used to compile OpenCL kernel. In Command Prompt window, type “cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add” to go to **vector_add** project folder, then type “**aoc device\vector_add.cl -o bin\vector_add.aocx --board de5a_net_i2**” to compile the OpenCL kernel. It will take about one hour for compiling. When the compilation process is finished, OpenCL image file vector_add.aocx is generated. **Figure 2-4** is the screenshot when OpenCL kernel is compiled successfully. For required parameters to compile vector_add.cl, please refer to the README.txt that is in the same folder as the vector_add.cl. For detailed usage of **aoc**, please refer to the **Altera SDK for OpenCL Programming Guide**:

https://www.altera.com/en_US/pdfs/literature/hb/opencl-sdk/aocl_programming_guide.pdf



```
Administrator: C:\Windows\system32\cmd.exe - aoc device\vector_add.cl -o bin\vector_add.aocx -...
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add
C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add>aoc device\vector_add.cl -o bin\vector_add.aocx --board de5a_net_i2
c:/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/device/vector_add.cl:23:48: warning: declaring kernel argument with no 'restrict' may lead to low kernel performance
    __kernel void vector_add(__global const float *x,
                           ^
c:/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/device/vector_add.cl:24:48: warning: declaring kernel argument with no 'restrict' may lead to low kernel performance
    __global const float *y,
                           ^
2 warnings generated.
```

Figure 2-4 “aoc vector_add.cl” OpenCL kernel compile

■ Compile Host Program

Visual Studio C/C++ 2012 is used to compile the Host Program. Launch Visual Studio, and select menu item “FILE→Open Project...”. In the Open Project dialog, go to the folder “C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add”, and select “vector_add.sln” as shown **Figure 2-5**.




Figure 2-5 Open vector_add.sln Host Program

After vector_add Host Program project is opened successfully, in Visual Studio IDE select menu item “BUILD→Build Solution” to build host program. When build is successfully, you will see successful message as show in **Figure 2-6**. The execute file is generate in:

“C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin\host.exe”





Figure 2-6 Message for vector_add Host Program build successfully

■ Test vector_add project

Firstly, use the compiled OpenCL image file `vector_add.aocx` to configure the FPGA. In Command Prompt window, type `cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin` to go to `vector_add\bin` project folder, then type `aoel program acld5a_net0 vector_add.aocx` to configure FPGA with the OpenCL Image `vector_add.aocx`. If configuration is successfully, you will see the successful message as shown in [Figure 2-7](#).



```
Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.


C:\Users\Administrator>cd C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin>aoel program acld5a_net0 vector_add.aocx
aoel program: Running program from C:\altera_pro\16.0\hld\board\de5a_net_i2\windows64/libexec
Setting debug level to 0
Programming device: de5a_net_i2 : Arria 10 Reference Platform (acld5a_net0)
Reprogramming device with handle 1
Program succeed.

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin>
```

Figure 2-7 “`aoel program acld5a_net0 vector_add.aocx`” configured successfully

In Command Prompt window, execute `host.exe`. [Figure 2-8](#) is the screen shot when the test is successful.



```
Administrator: C:\Windows\system32\cmd.exe

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin>host
Initializing OpenCL
Setting debug level to 0
Platform: Altera SDK for OpenCL
Using 1 device(s)
  de5a_net_i2 : Arria 10 Reference Platform (acld5a_net0)
Using AOCL: vector_add.aocx
Reprogramming device with handle 1
Launching for device 0 (1000000 elements)

Time: 7.481 ms
Kernel time (device 0): 3.835 ms

Verification: PASS

C:\altera_pro\16.0\hld\board\de5a_net_i2\tests\vector_add\bin>
```

Figure 2-8 “`vector_add`” test successfully

Chapter 3

OpenCL for Linux

This chapter describe how to setup DE5a-Net OpenCL development environment on 64-bit Linux (Red Hat Enterprise Linux 6.5/CentOS 7.0 are recommended), and how to compile and test the OpenCL examples for DE5a-Net. For more details about Altera OpenCL , please refer to Altera SDK for OpenCL Getting Started document:

https://www.altera.com/en_US/pdfs/literature/hb/openc1-sdk/aocl_getting_started.pdf

3.1 Software Installation

This section describes how to download and install the required software for OpenCL.

■ Altera Quartus II and OpenCL

Altera Quartus II Pro Edition Build 211 can be download from the web site:

<http://dl.altera.com/16.0/pro>

Altera Quartus II Pro Edition Build 222 and OpenCL SDK Build 222 linux update files can be download from the web site:

<http://dl.altera.com/openc1/16.0/>

open the link and select **Updates** table as **Figure 3-1** shows.


Intel SDK for OpenCL™

Release date: May, 2016

Latest Release: v16.1

Select release: 16.0

Download Method Akamai DLM3 Download Manager Direct Download




Download and install instructions: [Less](#)

1. If you haven't already installed the Quartus II software v16.0 and the Intel FPGA SDK for OpenCL, download and install them.
2. Download the software update file.
3. Change the file permission for all the setup (.run) files by running the command: `chmod +x *.run`.
4. Run the file.

Figure 3-1 Linux Update files selection

In the software download selection form, choose **Software and IP Updates(Latest)** as **Figure 3-2** show.



[Show Archived Software Updates](#)

Linux Update Files

- Software and IP Updates (Latest)**
 - Quartus Prime Software v16.0 Update 2**
*You must have the base software installed before installing the update.
Size: 6.1 GB MD5: 80A9D972CA35AE3A627C904CF85EB169
 - Altera SDK for OpenCL v16.0 Update 2**
Size: 285.7 MB MD5: F13ED5917CDA965796F6751360981985

Download Selected Files

Figure 3-2 Linux update files download

Quartus II software uses the built-in USB-Blaster II drivers on Linux to access USB-Blaster II download cable on DE5a-Net. but after installed the Quartus II software with built-in drivers, User need to change the port permission for USB-Blaster II via issuing

```
'gedit /etc/udev/rules.d/51-usbblaster.rules'
```

to create and add the following lines to the `/etc/udev/rules.d/51-usbblaster.rules` file.

```
# USB-Blaster
BUS=="usb", SYSFS{idVendor}=="09fb", SYSFS{idProduct}=="6001", MODE="0666"
BUS=="usb", SYSFS{idVendor}=="09fb", SYSFS{idProduct}=="6002", MODE="0666"
BUS=="usb", SYSFS{idVendor}=="09fb", SYSFS{idProduct}=="6003", MODE="0666"
# USB-Blaster II
BUS=="usb", SYSFS{idVendor}=="09fb", SYSFS{idProduct}=="6010", MODE="0666"
BUS=="usb", SYSFS{idVendor}=="09fb", SYSFS{idProduct}=="6810", MODE="0666"
```

Note: You must have system administration (root) privileges to configure the USB-Blaster download cable drivers.

■ GNU development tools

GNU development tools such as **gcc**(include **g++**) and **make** are required to build the driver and application under Linux. User can issue ‘yum install gcc ccompat-gcc-48-c++ make’ command to download and install them and their dependencies via internet.

Note: To install the SDK on Linux, you must install it in a directory that you own (that is, a directory that is not a system directory). You must also have sudo or root privileges.

■ DE5a-Net openCL BSP (Board Support Package)

After Quartus II and OpenCL SDK are installed, please download the DE5ANET_I2_OpenCL_BSP_16.0.tar.gz DE5a-Net linux BSP for Altera OpenCL 16.0 from the web:

<http://de5a-net.terasic.com/cd>

Then, decompress DE5ANET_I2_OpenCL_BSP_16.0.tar.gz to the “**de5a_net_i2**” folder under the folder “/root/altera_pro/16.0/hld/board”, where assumed Quartus II is installed on the folder “/root/altera_pro/16.0”, as shown in **Figure 3-3**.




Figure 3-3 DE5a-Net OpenCL BSP Content

3.2 OpenCL License Installation

An OpenCL license is required to compile the OpenCL projects for Altera OpenCL SDK. Developers can purchase the OpenCL license from either Altera or Terasic. Assuming that developers have obtained a license file with the filename “license.dat”, and it is saved in the local disk with the file path such as “/root/altera_pro/16.0/hld/license.dat”. The license can then be set up by creating an environment variable **LM_LICENSE_FILE**, and set its value as “/root/altera/16.0/hld/license.dat”.

Note that this environment value needs to correspond to the actual “license.dat” file location.

The next chapter will describe the license environment setting up.

3.3 Configure

If you install the ALTERA FPGA development software and OpenCL SDK on a system that does not contain any .cshrc or Bash Resource file (.bashrc) in your directory, you must set the ALTERAOCLSDKROOT and PATH environment variables manually. And for Altera OpenCL SDK able to find the kit location of DE5a-Net correctly, the developers need to create an environment variable for the DE5a-Net board **AOCL_BOARD_PACKAGE_ROOT**, and set its

value as:

```
"$ALTERAOCLSDKROOT"/board/de5a_net_i2"
```

Alternatively, you can edit the “/etc/profile” **profile** file, and append the environment variables to it. To do this type “*gedit /etc/profile*” *command on Linux Terminal* to open the **profile** file by the **gedit** editor tool, and append the following setting to the **profile** file. Then, save the file and type “*source /etc/profile*” *command in Linux Terminal* to make the settings make effect.

```
export QUARTUS_ROOTDIR=/root/altera_pro/16.0/quartus
export ALTERAOCLSDKROOT=/root/altera_pro/16.0/hld
export PATH=$PATH:"$QUARTUS_ROOTDIR"/bin:"$ALTERAOCLSDKROOT"/linux64/bin:"$ALTERAOCLSDKROOT"/bin: "$ALTERAOCLSDKROOT"/host/linux64/bin
export LD_LIBRARY_PATH="$AOCL_BOARD_PACKAGE_ROOT"/linux64/lib:"$ALTERAOCLSDKROOT"/host/linux64/lib
export AOCL_BOARD_PACKAGE_ROOT="$ALTERAOCLSDKROOT"/board/de5a_net_i2
export QUARTUS_64BIT=1
export LM_LICENSE_FILE=/root/altera_pro/16.0/hld/license.dat
```

3.4 Board Setup

Before testing OpenCL on DE5a-Net, please following the below procedure to setup DE5a-Net board on your PC as shown in **Figure 3-4**.

1. Make sure your PC is power off.
2. Insert DE5a-Net board into PCI Express x8 or x16 slot.
3. Connect PC’s 12V PCI Express 6-pin power to the DE5a-Net source (if there’s not, ignore this step)
4. Connector PC’s USB port to DE5a-Net mini USB port using an USB cable.

Note, the usb cable can be removed later if any one of OpenCL code had been programming to the startup configuration flash of DE5a-Net by ‘aocl flash’ command.




Figure 3-4 Setup DE5a-Net board on PC

3.5 OpenCL Environment Verify and Flash CVP

This section will show how to make sure the OpenCL environment is setup correctly.

Firstly, please open the Linux system **terminal** window by right click the Mouse on system desktop, then clicking on **Open Terminal**.


■ Target Board

In the Linux terminal, type “*aoc --list-boards*” command, and make sure “*de5a_net_i2*” is listed in **Board list** as shown in [Figure 3-5](#).

```
root@localhost:~/Desktop
File Edit View Search Terminal Help
[root@localhost Desktop]# aoc --list-boards
Board list:
  de5a_net_i2
[root@localhost Desktop]#
```

Figure 3-5 ‘de5a_net_i2’ is listed in Board list

Then type “*aocl install*” to load the PCIe driver for the DE5a-Net as shown in [Figure 3-6](#).



```
root@localhost:~/Desktop
File Edit View Search Terminal Help
[root@localhost Desktop]# aocl install
aocl install: Running install from /root/altera_pro/16.0/hld/board/de5a_net_i2/linux64/libexec
Using kernel source files from /lib/modules/3.10.0-327.22.2.el7.x86_64/build
Building driver for BSP with name de5a_net_i2
make: Entering directory `/usr/src/kernels/3.10.0-327.22.2.el7.x86_64'
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci_queue.o
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci.o
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci_fileio.o
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci_dma.o
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci_pr.o
  CC [M] /tmp/openccl_driver_7b1JaC/aclpci_cmd.o
  LD [M] /tmp/openccl_driver_7b1JaC/aclpci_de5a_net_i2_drv.o
Building modules, stage 2.
MODPOST 1 modules
  CC      /tmp/openccl_driver_7b1JaC/aclpci_de5a_net_i2_drv.mod.o
  LD [M] /tmp/openccl_driver_7b1JaC/aclpci_de5a_net_i2_drv.ko
make: Leaving directory `/usr/src/kernels/3.10.0-327.22.2.el7.x86_64'
[root@localhost Desktop]# █
```

Figure 3-6 driver installation

Note: if user don't using the recommended Linux system or different version, recompile the driver is needed. You can compile it by typing “*cd root/altera_pro/16.0/hld/board/de5a_net_i2/linux64/driver*” (there are source code, makefile and readme.txt) to locate at the driver source code directory and type “*./make_all*” to compile and generate the new driver. Before that, user need to install the kernel related development package matched the current kernel (**kernel-devel** package) via issuing ‘*yum install kernel-devel*’ command.

■ Test ‘aocl flash’ Command

In the terminal, type “*cd /root/altera_pro/16.0/hld/board/de5a_net_i2/tests/hello_world/bin*” to go to hello world OpenCL project folder, then type “*aocl flash aclde5a_net_i20 hello_world.aocx*” to program **hello_world.aocx** OpenCL image onto the startup configuration flash of DE5a-Net.

Before flash programming, the programmer will ask users which startup configuration image area will be used as shown in [Figure 3-7](#). This is because DE5a-Net provides two startup configuration image areas, called as Factory Image and User Image. Typing ‘1’ to select User Image area is recommended.

```
root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/hello_world/bin - □ ×
File Edit View Search Terminal Help
[root@localhost bin]# aocl flash acldede5a_net_i20 hello_world.aocx
aocl flash: Running flash from /root/altera_pro/16.0/hld/board/de5a_net_i2/linux
64/libexec
6M
===== Page Selection =====
Please select the flash page where to store your FPGA configure data:
[0] Factory Image Location(Address 0x00040000), SW3.4 = "1" (Right Position)
[1] User Image Location(Address 0x02B40000), SW3.4 = "0" (Left Position)
Enter a digital number 0 or 1 (Or other values to exit the program) followed by
pressing the "Enter" key:
1
Flash Programming...
Info: *****
Info: Running Quartus Prime Convert_programming_file
Info: Version 16.0.2 Build 222 07/20/2016 SJ Pro Edition
Info: Copyright (C) 1991-2016 Altera Corporation. All rights reserved.
Info: Your use of Altera Corporation's design tools, logic functions
Info: and other software and tools, and its AMPP partner logic
Info: functions, and any output files from any of the foregoing
Info: (including device programming or simulation files), and any
Info: associated documentation or information are expressly subject
Info: to the terms and conditions of the Altera Program License
Info: Subscription Agreement, the Altera Quartus Prime License Agreement,
Info: the Altera MegaCore Function License Agreement, or other
```

Figure 3-7 Select Flash Page

After selecting the desired flash area, it will take about 20 minutes for flash programming. **Figure 3-8** is the screen shot when flash programming is done successfully.

```
root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/hello_world/bin - □ ×
File Edit View Search Terminal Help
Info (209005): Programming status: programming flash memory at byte address 0x0F
F80000
Info (209005): Programming status: programming flash memory at byte address 0x0F
F90000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FA0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FB0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FC0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FD0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FE0000
Info (209005): Programming status: programming flash memory at byte address 0x0F
FF0000
Info (209011): Successfully performed operation(s)
Info (209061): Ended Programmer operation at Sat Feb 4 14:54:09 2017
Info: Quartus Prime Programmer was successful. 0 errors, 0 warnings
Info: Peak virtual memory: 3305 megabytes
Info: Processing ended: Sat Feb 4 14:54:09 2017
Info: Elapsed time: 00:14:21
Info: Total CPU time (on all processors): 00:02:23
[root@localhost bin]#
```

Figure 3-8 ‘aocl flash acldede5a_net_i20 hello_world.aocx’ successfully

To make sure correct image is used when FPGA boot, please make sure the dip switch SW3.4 on DE5a-Net is located at correct location. If User Image area is selected, the dip switch SW3.4 on the DE5a-Net should be move to **up** position as shown in [Figure 3-9](#).




Figure 3-9 Set SW3.4 to Left Position (User Image Page)

After flash programming is done successfully and SW3.4 is set to correct position, developers can power off PC and DE5a-Net board, then turn it back on.

■ Test ‘aocl diagnose’ Command

The diagnose utility in the Arria 10 DE5a-Net board reports device information and identifies issues. The diagnose utility first verifies the installation of the kernel driver and returns the overall information of all the devices installed in a host machine.

In the Linux terminal, type ”**aocl diagnose**” to check if the initialization completed successfully. If successful, the programming message displays “**DIAGNOSTIC_PASSED**” as shown in [Figure 3-10](#).


```
root@localhost:~/Desktop
File Edit View Search Terminal Help
[root@localhost Desktop]# aocl diagnose
aocl diagnose: Running diagnose from /root/altera_pro/16.0/hld/board/de5a_net_i2/
linux64/libexec

----- acl0 -----
Vendor: Terasic

Phys Dev Name   Status   Information
aclde5a_net_i20 Passed   Arria 10 Reference Platform (aclde5a_net_i20)
                                   PCIe dev_id = 2494, bus:slot.func = 01:00.00, Gen3 x8
                                   FPGA temperature = 33.293 degrees C.

DIAGNOSTIC_PASSED
-----

[root@localhost Desktop]# █
```

Figure 3-10 “aocl diagnose” messages

Note: For DE5a-Net to negotiate with the host PC at Gen 3 as the link speed, it is strongly recommended that users set the PCIe speed at Gen 3 in the BIOS on the host PC. If your PC support PCIe Gen3x8, but detected is incorrect, you can modify the PCIe settings in the BIOS, and reboot.

■ Test ‘aocl program’ Command

Check whether the **hello_world** OpenCL image, which is CvP enabled, configures the FPGA successfully when DE5a-Net is power on. In the Linux terminal, type “*cd /root/altera_pro/16.0/hld/board/de5a_net_i2/tests/hello_world/bin*” to go to hello_world project folder, then type “*aocl program aclde5a_net_i20 hello_world.aocx*” to configure the FPGA with **hello_world.aocx** OpenCL image. If the programming message displays “Program succeed” as shown in **Figure 3-10**, it means the **hello_world** OpenCL image is programmed into the flash correctly and CvP works well.

```
root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/hello_world/bin
File Edit View Search Terminal Help
[root@localhost bin]# aocl program aclde5a_net_i20 hello_world.aocx
aocl program: Running program from /root/altera_pro/16.0/hld/board/de5a_net_i2/l
inux64/libexec
Programming device: de5a_net_i2 : Arria 10 Reference Platform (aclde5a_net_i20)
Reprogramming device with handle 1
Program succeed.
[root@localhost bin]# █
```

Figure 3-10 ‘aocl program aclde5a_net_i20 hello_world.aocx’ use CvP

3.6 Compile and Test OpenCL Project

This section will show how to compile and run the OpenCL kernel and OpenCL Host Program for the `vector_add` example project. Developers can use the same procedures to compile and test other OpenCL examples (included in the kit) for DE5a-Net.

■ Compile OpenCL Kernel

In the terminal, type `cd /root/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add` to go to `vector_add` project folder, then type `aoc device/vector_add.cl -o bin/vector_add.aocx --board de5a_net_i2 --report` to compile the OpenCL kernel. It will takes about one hour for compiling. After that, the OpenCL image file `vector_add.aocx` is generated. **Figure 3-11** is the screen shot when OpenCL kernel is compiled successfully. For required parameters to compile `vector_add.cl`, please refer to the `README.txt` that is in the same directory.

The utility `aoc` (Altera SDK for OpenCL Kernel Compiler) is used to compile OpenCL kernel. For detailed usage of `aoc`, please refer to the **Altera SDK for OpenCL Programming Guide**:

http://www.altera.com/literature/hb/opencl-sdk/aocl_programming_guide.pdf

```

root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add
File Edit View Search Terminal Help
[root@localhost vector_add]# aoc device/vector_add.cl -o bin/vector_add.aocx --board de5a_net_i2 --report
aoc: Selected target board de5a_net_i2
/root/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/device/vector_add.cl:23:48: warning: declaring kernel argument with no 'restrict' may lead to low kernel performance
__kernel void vector_add(__global const float *x,
                        ^
/root/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/device/vector_add.cl:24:48: warning: declaring kernel argument with no 'restrict' may lead to low kernel performance
                        __global const float *y,
                        ^
2 warnings generated.

+-----+
; Estimated Resource Usage Summary
+-----+
; Resource          + Usage
+-----+
; Logic utilization ; 23%
; ALUTs             ; 9%
; Dedicated logic registers ; 14%
; Memory blocks    ; 10%
; DSP blocks       ; 4%
+-----+

```

Figure 3-11 ‘aoc vector_add.cl” OpenCL kernel compile successfully

■ Compile Host Program

In the terminal, type “`cd /root/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add`” and then type “*make*” to compile the host program.

When build is successfully, you will see successful message as show in [Figure 3-12](#). The execute file is generate in the same directory which named bin.

```

root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add
File Edit View Search Terminal Help
[root@localhost vector_add]# make
[root@localhost vector_add]# █


```

Figure 3-12 successful Message for vector_add Host Program build

■ Test vector_add project

Firstly, In the terminal, type “`cd /root/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/bin`” to go to the **vector_add** project folder, then type “`aocl program aclde5a_net_i20 vector_add.aocx`” to configure FPGA with the OpenCL Image vector_add.aocx.

Then, launch the compiled Host Program to start vector_add execute file for test. In the terminal type “`./host`”. **Figure 3-13** shows the execution is successful.

A terminal window screenshot showing the execution of an OpenCL program. The window title is "root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/bin". The terminal output shows the command "aocl program aclde5a_net_i20 vector_add.aocx" being executed, followed by "aocl program: Running program from /root/altera_pro/16.0/hld/board/de5a_net_i2/linux64/libexec". It then displays "Programming device: de5a_net_i2 : Arria 10 Reference Platform (aclde5a_net_i20)", "Reprogramming device with handle 1", and "Program succeed.". The next command is "./host", which outputs "Initializing OpenCL", "Platform: Altera SDK for OpenCL", "Using 1 device(s)", "de5a_net_i2 : Arria 10 Reference Platform (aclde5a_net_i20)", "Using AOCX: vector_add.aocx", "Reprogramming device with handle 1", and "Launching for device 0 (1000000 elements)". The execution time is shown as "Time: 6.425 ms" and "Kernel time (device 0): 3.523 ms". The final output is "Verification: PASS" and the prompt "[root@localhost bin]#" is visible.

```
root@localhost:~/altera_pro/16.0/hld/board/de5a_net_i2/tests/vector_add/bin
File Edit View Search Terminal Help
[root@localhost bin]# aocl program aclde5a_net_i20 vector_add.aocx
aocl program: Running program from /root/altera_pro/16.0/hld/board/de5a_net_i2/linux64/libexec
Programming device: de5a_net_i2 : Arria 10 Reference Platform (aclde5a_net_i20)
Reprogramming device with handle 1
Program succeed.
[root@localhost bin]# ./host
Initializing OpenCL
Platform: Altera SDK for OpenCL
Using 1 device(s)
  de5a_net_i2 : Arria 10 Reference Platform (aclde5a_net_i20)
Using AOCX: vector_add.aocx
Reprogramming device with handle 1
Launching for device 0 (1000000 elements)

Time: 6.425 ms
Kernel time (device 0): 3.523 ms

Verification: PASS
[root@localhost bin]#
```

Figure 3-13 successful Message for “vector_add” test